

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

Claim 1 (currently amended): A method for compensating for backlight conditions in a scene for use in a camera that includes a flash and a flash control signal for activating the flash when the flash control signal is asserted, the method comprising the steps of:

a) generating a meter matrix for a scene that includes a plurality of points, wherein each point includes brightness information and distance information[[: and]]; said generating comprising:

defining a subject group of points;

defining a background group of points;

generating at least one point in the subject group;

generating at least one point in the background group; and

~~b) selectively asserting a flash control signal based on the meter matrix;~~

determining the distance between the camera and the point in the subject group;

determining whether the distance between the camera and the point in the subject group is less than a predetermined distance;

when the distance between the camera and the point in the subject group is less than a predetermined distance;

determining a general brightness level of the scene;

determining whether the general brightness level exceeds a predetermined brightness threshold; and

when the general brightness level exceeds a predetermined brightness threshold, asserting the flash control signal.

Claim 2 (cancelled)

Claim 3 (currently amended) The method of claim 1 [[2]] and further comprising: wherein the step of selectively asserting a flash control signal based on the meter matrix includes the steps of:

~~a) determining the distance between the camera and the point in the subject group;~~

b) determining the distance between the camera and the point in the background group; and

c) determining the difference between the distance between the camera and the point in the background group and the distance between the camera and the point in the subject group.

Claim 4 (currently amended): The method of claim 3 and further comprising: wherein the step of selectively asserting a flash control signal based on the meter matrix further includes the steps of:

determining the brightness of the point in the subject group;

determining the brightness of the point in the background group; and

determining the difference between the brightness of the point in the background group and the brightness in the subject group.

Claim 5 (currently amended): The method of claim 4 and further comprising: wherein the step of selectively asserting a flash control signal based on the meter matrix further includes the steps of:

determining whether the distance difference exceeds a predetermined distance threshold;

determining whether the brightness difference exceeds a predetermined brightness threshold; and

when the distance difference exceeds a predetermined distance threshold and when the brightness difference exceeds a predetermined brightness threshold,

asserting the flash control signal.

Claim 6 (currently amended): The method of claim 1 [[2]] wherein the background points form an inverted "U" shape and the subject group of points form an "I" shape.

Claim 7 (cancelled)

Claim 8 (currently amended): The method of claim 1 [[7]] wherein the step of determining the distance between the camera and the point in the subject group includes

employing a spot focus sensor for measuring the distance between the camera and the point in the subject group.

Claim 9 (currently amended): The method of claim 1 [[7]] wherein the step of determining a general brightness level of the scene includes

employing a general light sensor for measuring the general brightness level of the scene.

Claim 10 (original): The method of claim 1 wherein the camera is one of a digital camera, a film camera, an image sensor.

Claim 11 (currently amended): A camera for capturing a scene, said camera comprising:

a) a flash for emitting light in response to an asserted flash control signal;  
a scene separator for separating the plurality of points in a scene into a subject group and a background group;

b) a meter matrix generator for generating a meter matrix based on information received from the scene; wherein the meter matrix includes a plurality of points; wherein each point includes distance information and brightness information; and

~~c) a backlight compensation unit coupled to the meter matrix generator for receiving the meter matrix and for selectively asserting the flash control signal based on the matrix meter.~~

a brightness evaluator for selectively asserting the flash control signal based on brightness information of a point in the subject group and a point in the background group; and

a distance evaluator for selectively asserting the flash control signal based on distance information of a point in the subject group and a point in the background group.

Claim 12 (cancelled)

Claim 13 (currently amended): The camera of claim 11 ~~[[12]]~~ wherein the distance evaluator determines the distance between the camera and the point in the subject group, determines the distance between the camera and the point in the background group, and determines the difference between the distance between the camera and the point in the background group and the distance between the camera and the point in the subject group.

Claim 14 (currently amended): The camera of claim 13 and further comprising a brightness compensation unit, wherein the brightness evaluator determines the brightness of the point in the subject group, determines the brightness of the point in the background group, and determines the difference between the brightness of the point in the background group and the brightness of the point in the subject group; wherein the backlight compensation unit determines whether the distance difference exceeds a predetermined distance threshold and determines whether the brightness difference exceeds a predetermined brightness threshold, and when the distance difference exceeds a predetermined distance threshold and when the brightness difference exceeds a predetermined brightness threshold, asserting the flash control signal.

Claim 15 (currently amended): The camera of claim 11 ~~[[12]]~~ wherein the distance evaluator determines the distance between the camera and the point in the subject group, determines whether the distance between the camera and the point in the subject group is less than a predetermined distance, when the distance between the camera and the point in the subject group is less than a predetermined distance, employing the brightness evaluator to determine a general brightness level of the scene, determine whether the general brightness level exceeds a predetermined brightness threshold, and when the general brightness level exceeds a predetermined brightness threshold, asserting the flash control signal.

Claim 16 (original): The camera of claim 15 further comprising:  
a spot focus sensor for measuring the distance between the camera and the point in the subject group; and  
a general light sensor for measuring the general brightness level of the scene.

Claim 17 (original): The camera of claim 11 further comprising:  
means for measuring distance information of the scene; and  
means for measuring brightness information of the scene.

Claim 18 (currently amended): The camera of claim 11 ~~[[1]]~~ wherein the camera is one of a digital camera and a film camera.

Claim 19 (currently amended): A camera for capturing a scene, said camera comprising:

- a) means for emitting light in response to an asserted flash control signal;
- b) means for generating a meter matrix based on information received from the scene; wherein the meter matrix includes a plurality of points; wherein each point includes distance information and brightness information; and
- c) backlight compensation means coupled to the meter matrix generator for receiving the meter matrix and for selectively asserting the flash control signal based on

the matrix meter[[]], the backlight compensation means further comprising:

means for separating the plurality of pints in a scene into a subject group and a background group;

brightness evaluation means for selectively asserting the flash control signal based on brightness information of a point in the subject group and a point in the background group; and

distance evaluation means for selectively asserting the flash control signal based on distance information of a point in the subject group and a point in the background group.

Claim 20 (cancelled)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**